

FlatLED T2

Surface Mounted

Type	Downlight
Mounting	Surface mounted
Material	Aluminium
Adjustability	Cardanic/Gimble
El. class / IP	Class I / IP20

Bridgelux ES Rectangle LED

LED Module included

Driver included

CCT	2700K / 3000K
CRI	Ra80 / Ra90
Luminous flux	2700K - Ra80: 1420lm (97lm/W) 2700K - Ra90: 1200lm (82lm/W) 3000K - Ra80: 1540lm (105lm/W)
Beam angle	24 / 32°
Power	14.7W
Cooling	Passive (no fan)
SDCM	3
	5 Year Bridgelux Warranty on Bridgelux LEDs ⁽¹⁾

⁽¹⁾ Limited warranty. More information on p.268



On Request

Other RAL colors



FlatLED T2

Surface Mounted

Bridgelux LED - Non dimmable

2700K - Ra80 - 14.7W - 1420lm 468.AA.24.827.xx
 2700K - Ra90 - 14.7W - 1200lm 468.AA.24.927.xx
 3000K - Ra80 - 14.7W - 1540lm 468.AA.24.830.xx

Bridgelux LED - 1-10V dimmable

2700K - Ra80 - 14.7W - 1420lm 468.AA.24.827.xx
 2700K - Ra90 - 14.7W - 1200lm 468.AA.24.927.xx
 3000K - Ra80 - 14.7W - 1540lm 468.AA.24.830.xx

Bridgelux LED - DALI dimmable

2700K - Ra80 - 14.7W - 1420lm 468.AA.26.827.xx
 2700K - Ra90 - 14.7W - 1200lm 468.AA.26.927.xx
 3000K - Ra80 - 14.7W - 1540lm 468.AA.24.830.xx

Bridgelux LED - Mains dimmable

2700K - Ra80 - 14.7W - 1420lm 468.AA.27.827.xx
 2700K - Ra90 - 14.7W - 1200lm 468.AA.27.927.xx
 3000K - Ra80 - 14.7W - 1540lm 468.AA.27.830.xx

Bridgelux LED - Push dimmable

2700K - Ra80 - 14.7W - 1420lm 468.AA.29.827.xx
 2700K - Ra90 - 14.7W - 1200lm 468.AA.29.927.xx
 3000K - Ra80 - 14.7W - 1540lm 468.AA.29.830.xx

28° Reflector: 0000.28.00.0000.00

40° Reflector: 0000.40.00.0000.00

Available colors: 000.00.00.0000.xx

Other RAL colors on request



01 White Matt Texture Standard



03 Black Matt texture Standard



05 White + Black Standard



07 Anthracite Matt Text. Grey Matt Texture

